

4 IN 1 BULLET CAMERA, 2 MP

CVBS HDCVI™

HDTVI AHD



FEATURES

- Full HD resolution with Sony® CMOS sensor
- IR illumination up to 20 meters
- 2.8 mm fixed lens
- Transmission distance up to 300 (theoretical) meters
- AWB, AGC, BLC, HLC, digital WDR
- OSD menu
- 4 in 1 output (OSD switch): CVBS, HDCVI, HDTVI, AHD
- IP66
- 3AXIS bracket with cable passage

CAMERA

Image sensor	1/3" Sony® Exmor CMOS, 2 MP
Effective pixels	1920(H) x 1080(V)
Synchronization	Internal
Frames per second	PAL/NTSC: 25/30 fps @1080P
Electronic shutter	1/50s ~ 1/50.000s, 1/60s ~ 1/60.000s
IR illumination	23 leds Ø5 mm: 20 meters
Minimum illumination	0,01 lux F1,2 (AGC On) / 0 lux IR ON
Video output	AHD, HD-CVI, HD-TVI, 1 BNC CVBS (OSD switch)

LENS

Lens	2,8 mm
Viewing angle	90°

FUNCTIONS

Day/night	Auto (ICR)
OSD menu	Supported
White balance	AWB
Gain control	AGC
Backlight compensation	BLC, HLC, digital WDR

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%) /700 mA
Consumption	8W
Working temperature	-10°C ~ +55°C
RH	<95% HR
Transmission distance	Up to 300 meters (theoretical) via 75-3 coaxial cable
Protection	IP66

PHYSICAL FEATURES

Dimensions	Ø68,48 x 64 x 187,34 mm
------------	-------------------------

ACCESORIES



HYU-254
Connection base

DIMENSIONS

